

## Only one system for safety railing!

### Protection railing with Uni-clamp

- Certified according to EN 13374 Class A"
- Quick and easy protection
- Board holder is 360° turnable
- Toe board holder can be adjusted in height
- Universal for any protection railing
- Durable due to hot-dip galvanization
- Strong connection due to triple windnut
- Slab thickness max 40 cm (for Uni-clamp)

### Layout according to regulations of BAUV

- |                  |                     |                  |
|------------------|---------------------|------------------|
| - Interval 1,5 m | Boards for parapets | min. 15 x 2,4 cm |
| - Interval 2,0 m | Toe boards          | min. 15 x 3,0 cm |
|                  |                     | min. 15 x 2,0 cm |

### Protection railing for anchor sleeve set in concrete

- all existing DW15 sleeves can be used.
- concrete strength min. 10N/mm<sup>2</sup>

#### Possible application:

Balkonies, slab edges, cornices, stringers

#### Angle adaptor

It is used to fix protection railing to the slab side. Screw adaptor in anchor sleeve and fix firmly with triple windnut against contortion to the slab.

Easy protection!

Ankerhülse

angle adaptor

| Item                                                        | Art.-Nr. | Weight  |
|-------------------------------------------------------------|----------|---------|
| Protection railing screwable galvanized                     | 230V7    | 2,80 kg |
| UNI-clamp galvanized                                        | 230V8    | 4,50 kg |
| Angle adaptor galvanized                                    | 230V9    | 1,00 kg |
| Anchor sleeve DW15 Alu L = 19 cm<br>(incl. nail plates PVC) | 254      | 0,07 kg |

AN 01/16